

CVAC HV industrial high vacuum vacuums for centralized systems

CENTRALIZED VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



- ✓ Equipped as standard with an electrical panel with star-delta starting and local/remote control, pressure relief valve and soundproofing guard.

Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	12,6 - 15 - 21,3
Maximum depression	mmH2O	5.100 - 6.000 - 5.000
Continuous depression	mmH2O	4.300 - 5.400 - 4.400
Maximum air flow rate	m3/h	520 - 720 - 1.180
Nozzle	mm	70 - 100
Noisiness (EN ISO 3744)	dB(A)	74 - 77 - 78

Filter Unit

Collection unit

Encumbrances

Dimensions	cm	89x78x124h - 103x93x197h
------------	----	--------------------------

APPLICATIONS: Cementitious Sandblasting Steel mills and foundries



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC HV industrial high vacuum vacuums for centralized systems

CENTRALIZED VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

SUCTION UNIT

The suction unit is equipped with a volumetric vacuum pump with trilobe rotors capable of generating very high vacuum and air flow rates

OPTIONALS

- ✓ Hepa safety filter h14 52,000cm2
- ✓ Hepa safety filter h14 103,000cm2