

Fumebuster AC – Activated Carbon Welding Vacuum Cleaner

AIR FILTRATION SOLUTIONS



✓ Accessories included, ideal for cleaning professionals.

Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	1,5
Maximum air flow rate	m3/h	1300
Nozzle	mm	150
Noisiness (EN ISO 3744)	dB(A)	72

Filter Unit

Cleaning system	Handbook
Filtration efficiency	F9 95%

Collection unit

Collection container	Painted
Cyclonic unit	Integrated
Exhaust system	Disposable bag

Encumbrances

Dimensions	cm	65 x 75 x 129h
Weight	kg	131

APPLICATIONS: Mechanical industry Steel mills and foundries



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Fumebuster AC – Activated Carbon Welding Vacuum Cleaner

AIR FILTRATION SOLUTIONS

SUCTION UNIT

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

FILTER UNIT

The vacuum cleaner is equipped with a progressive filtration consisting of panel filters with 4 stages of filtration.

COLLECTION UNIT

Container made entirely of AISI 316 stainless steel

OPTIONALS

- ✓ Local remote start-up
- ✓ Local/remote control
- ✓ Stainless steel chamber