

Oilvac 500 vacuum cleaner for coolant, oil and chips

INDUSTRIAL VACUUMS



- ✓ Designed for complete cleaning of CNC machines, all in one vacuum.

Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	4
Maximum depression	mmH2O	3.200
Continuous depression	mmH2O	2.400
Maximum air flow rate	m3/h	420
Limiting valve		Integrated
Noisiness (EN ISO 3744)	dB(A)	75

Filter Unit

Cleaning system		Handbook
Degree of chip filtration	µm	50

Collection unit

Liquid capacity	lt	500
Float		Electric
Collection system		Removable drawer
Exhaust system		Immersion pump
Solids capacity	lt	75

Encumbrances

Dimensions	cm	182x101x134h
Weight	kg	520

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Oilvac 500 vacuum cleaner for coolant, oil and chips

INDUSTRIAL VACUUMS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTER UNIT

Solids and chips are separated in an integrated container, whereas liquids are purified by means of a NW filter cloth.

COLLECTION UNIT

Possibility of cleaning the emptied tank with an adjustable high-pressure lance.

Independent 200l/min pump for re-injecting the emulsifier into the tank.