


WD 3000 AIR compressed air vacuum cleaner

INDUSTRIAL VACUUMS



- ✓ 100% steel construction.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Easy-to-empty detachable container.

Suction Unit

Maximum depression	mmH2O	3.700
Maximum air flow rate	m3/h	300 - 150
Nozzle	mm	50
Air supply	nlt/min (nm ³ /h)	729 - 1458
Air supply pressure	bar	6
Air supply hose	mm	12

Filter Unit

Primary filter		Sack
Surface area - diameter	cm ² -mm	8.000 - 400
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Capacity	lt	60
Collection system		Tipping container

Encumbrances

Dimensions	cm	72 x 56 x 94h
------------	----	---------------

APPLICATIONS: Sandblasting



General housekeeping



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

WD 3000 AIR compressed air vacuum cleaner

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTER UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.