

Oilvac 200 aspiratore industriale a benna

INDUSTRIAL VACUUMS



- ✓ Save money by recovering and reusing cutting oil and emulsion.
- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.
- ✓ Liquid level monitored by a floating device to stop when the container is full.

Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	3 x 1,1 - 2 x 1,6
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	540
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	14.000 - 420
Filter media - class	IEC 60335-2-69	M ANT Hydro-oleo repellent

Collection unit

Dust capacity	lt	30
Liquid capacity	lt	200
Float		Electric
Exhaust system		Immersion pump

Encumbrances

Dimensions	cm	122x62x130h
Weight	kg	205

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Oilvac 200 aspiratore industriale a benna

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

A float stops the suction when the liquid in the container reaches the maximum level, preventing spillage.

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

OPTIONALS

- ✓ Ppl oil filtration kit up to 100 microns (suction)