

ATEX certified vacuum units for suction systems

INDUSTRIAL VACUUMS



✓ Compliance to EN IEC 62784:2018 for zone 22

Suction Unit

ATEX Zones		Zone 22 Powders
Power supply	V - Hz	400 - 50 ~ 3
Zone use		Hazardous location
EX Category		CE EX 22 1/3D
Power	kW	4,6 - 25
Maximum depression	mmH2O	4.400 - 2.600
Maximum air flow rate	m3/h	2.050 - 420
Limiting valve		Integrated
Noisiness (EN ISO 3744)	dB(A)	74 - 81

Filter Unit

Cleaning system	Handbook
-----------------	----------

Collection unit

Encumbrances

Dimensions	cm	67-83x63-93x124-197h
------------	----	----------------------

APPLICATIONS: Cementitious  Food, chemical and pharmaceutical industry Sandblasting Steel mills and foundries



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

ATEX certified vacuum units for suction systems

INDUSTRIAL VACUUMS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

OPTIONALS

- ✓ Additional silencer
- ✓ Inverter
- ✓ Hepa safety filter h14 103,000cm2
- ✓ Hepa safety filter h14 52,000cm2