

Oilvac 130P vacuum for CNC with drain pump

INDUSTRIAL VACUUMS



- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.

Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	3 x 1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	540
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	14.000 - 420
Filter media - class	IEC 60335-2-69	M ANT Hydro-oleo repellent

Collection unit

Dust capacity	lt	30
Liquid capacity	lt	130
Float		Electric
Exhaust system		Electric pump 100lt/mt

Encumbrances

Dimensions	cm	70x62x144h
Weight	kg	90

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Oilvac 130P vacuum for CNC with drain pump

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

The suction nozzle is tangential and the internally welded cyclone promotes partial suppression of the extracted dust and chips, ensuring excellent filter protection.

COLLECTION UNIT

Finer chips are retained by an additional basket fitted with a PPL filter which removes any impurities from the oil/emulsion.

A grid basket inside the container separates solids (chips, metal swarf) from liquids, which drain to the bottom of the container. The liquid is quickly disposed of via a manual liquid drain valve.

OPTIONALS

- ✓ Ppl oil filtration kit up to 100 microns (suction)